



ULTRA CLEAN®

Surface Cleaner - Fast

R7K158

PRODUCT DESCRIPTION:

UltraClean® Surface Cleaner R7K158 is a fast-evaporating solvent wash developed to maximize shop's productivity by decreasing surface preparation time. UltraClean® is used to remove wax, oil, grease and silicone contaminants for all:

- Bare metal substrates to prepare for primer
- Cured enamel or lacquer finishes to prepare for finishing
- Removes sanding residue before recoating

TECHNICAL DATA:

• VOC – as packaged	6.20 lbs/gal (743 g/l)	• Weight/gallon	6.20 lbs/gal
• Mixing Ratio	Use at package consistency	• Flash point	44°F TCC
• Freeze Hazard	No		

APPLICATION:

1. Saturate a clean cloth with UltraClean® R7K158.
2. Apply to areas to be painted and adjacent panels. Wipe surface thoroughly with UltraClean® R7K158 and apply only to one panel at a time.
3. Wipe off with a second clean, dry cloth before UltraClean® R7K158 is allowed to dry. If drying occurs, repeat application.
4. Should be used before sanding and can also be used after sanding prior to sealing or topcoating.

FEATURES:

1. Solvent cleaner
2. Mild solvent – mild odor
3. Faster evaporation

ADVANTAGES:

1. Removes wax, oil, grease and silicone.
2. Does not swell or soak into the surface. Does not burn. Does not remove Acrylic Lacquer color.
3. Less time required to clean vehicle.

BENEFITS:

1. Eliminates fisheye cratering that would require rework or the addition of fisheye eliminator. Promotes adhesion.
2. Eliminates sand scratch swelling from too strong of a solvent that would require rework or additional coats of topcoat. Eliminates color sanding, buffing longer and using more compound.
3. Increases shop production time.

P
R
O
D
U
C
T

D
A
T
A