



**SHERWIN-WILLIAMS**  
Automotive Finishes

## Plastic Surface Cleaner / Anti-static SC159

### PRODUCT DESCRIPTION:

Plastic Surface Cleaner / Anti-static SC159 is a solvent based cleaner specifically designed to remove solvent borne contaminants, while deep cleaning the plastic substrate to remove impregnated mold release agents. Plastic Surface Cleaner / Anti-static SC159 also removes static build up before painting.

### SURFACE PREPARATION:

Wash surfaces to be painted including adjacent panels with a mild detergent and water solution to remove heavy deposits of dirt, oil, and grease.



#### MIXING:


No mixing required in areas with a VOC limit above 0.21lbs/gal.

*\* If a VOC level of 0.21 lbs/gal is required, Aerosol Plastic Surface Degreaser SC160 can be used*




#### APPLICATION

- Clean all surfaces thoroughly with Plastic Surface Cleaner / Anti-static SC159 and a gold nylon scuff pad.
- Dry excess with a clean cloth.
- Apply a second application following the procedure listed above
- Tack surface to be painted with a clean tack cloth




#### RECOAT

- Make sure Plastic Surface Cleaner / Anti-static SC159 has been completely removed and panel is dry before painting.



#### NOTES

- Plastic Surface Cleaner / Anti-static SC159 is not recommended for use on solvent sensitive substrates such as lacquer, as softening will occur.
- For best results maintain an ambient temperature of 70° F when using Plastic Surface Cleaner / Anti-static SC159.



## PERSONAL PROTECTION

- For use by trained professionals only.
- Read label, directions, and MSDS before use.
- Use appropriate Personal Protective Equipment while mixing and spraying.

REGULATORY DATA	As Packaged	
	Lb/Gal	G/L
Density	7.07	847
	% by Wt.	% by Vol.
Volatiles	100	100
Water	0	0
Exempt Compounds	0	0
	Lb/Gal	G/L
VOC Total	7.07	847
VOC Less Exempt	6.72	847
	Lb/Gal	KG/L
HAPs	0.00	0.00

## LABEL CAUTION INFORMATION

### SC159

**DANGER! FLAMMABLE! HARMFUL IF INHALED - MAY AFFECT THE BRAIN OR NERVOUS SYSTEM, CAUSING DIZZINESS, HEADACHE OR NAUSEA. IRRITATES EYES, SKIN AND RESPIRATORY TRACT. CAN BE ABSORBED THROUGH THE SKIN.**

Contents are **FLAMMABLE**. Vapors may cause flash fires. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. **VAPOR HARMFUL**. Use only with adequate ventilation. Wear an appropriate properly fitted vapor/particulate respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID: If INHALED:** If affected, remove from exposure. Restore breathing, Keep warm and quiet. If on **SKIN:** Wash affected area thoroughly with soap and water. Remove contaminated clothing. Launder before re-use. If in **EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention. If **SWALLOWED:** Call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. FOR PROFESSIONAL USE ONLY. SEE MATERIAL SAFETY DATA SHEET.**